

**ICEA STANDARD FOR**  
**RISER CABLES**  
**TECHNICAL REQUIREMENTS**

Published By

**INSULATED CABLE ENGINEERS ASSOCIATION, INC.**

Post Office Box 1568

Carrollton, GA 30112, U.S.A.

© 2005

Approved June 28, 2004 by  
Insulated Cable Engineers Association, Inc.

Approved January 31, 2005 by  
American National Standards Institute

Copyrighted by the ICEA  
Contents may not be reproduced  
in any form without permission of the  
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

GLOBAL ENGINEERING DOCUMENTS  
15 Inverness Way East  
Englewood, CO 80113-5776 USA  
Telephone: (800) 854-7179  
[www.global.ihs.com](http://www.global.ihs.com)

## **NOTICE AND DISCLAIMER**

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

(page intentionally left blank)

## **FOREWORD**

ICEA Standards are published in the public interest and are intended to promote product uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of wire made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of wires defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions of interpretation of ICEA Standards can only be accepted in writing, and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary  
Insulated Cable Engineers Association, Inc.  
Post Office Box 1568  
Carrollton, GA 30112, U.S.A.  
United States of America

This Standard was approved by ICEA on June 28, 2004. The members of the ICEA Communications Cable Section, Working Group 701, who participated in this project, were:

Todd Rhoades, Chairman

D.K. Baker  
G. L. Dorna  
J. Kincaid  
P. Peterson

J. Cancelosi  
L. Hazy  
L. Lisker  
J. Shinoski

K. Chauvin  
F. Jean  
T. McLaughlin

The following participated in an advisory capacity to Working Group 701:

G. Hessler                      RUS

(page intentionally left blank)

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
1.	GENERAL .....	1
	1.1 PURPOSE .....	1
	1.2 SCOPE .....	1
	1.3 OPTIONS AND INFORMATION .....	1
	1.4 UNITS AND TOLERANCES .....	2
	1.5 TESTING CONDITIONS .....	2
	1.6 REFERENCES .....	2
	1.7 QUALITY ASSURANCE .....	2
	1.8 SAFETY CONSIDERATIONS .....	3
	1.9 INSTALLATION PRECAUTIONS .....	3
2.	CONDUCTORS .....	3
	2.1 CONDUCTOR TYPE .....	3
	2.2 CONDUCTOR DIAMETERS .....	3
	2.3 CONDUCTOR ELONGATION .....	3
	2.4 FACTORY JOINTS .....	3
3.	CONDUCTOR INSULATION .....	4
	3.1 INSULATION MATERIAL .....	4
	3.1.1 Heavy Metal Free Insulation Material .....	4
	3.1.2 Halogen or Nonhalogen Insulation Material .....	4
	3.2 INSULATION DIMENSIONS, COLORS, AND SPLICES .....	4
	3.2.1 Dimensions .....	4
	3.2.2 Colors .....	4
	3.2.3 Splices .....	4
	3.3 INSULATION PHYSICAL REQUIREMENTS .....	5
	3.3.1 Adhesion .....	5
	3.3.2 Tensile Strength and Elongation .....	5
	3.3.3 Compression .....	5
	3.3.4 Cold Bend .....	5
	3.3.5 Shrinkback .....	5
	3.3.6 Heat Exposure (Aging) .....	5
	3.3.7 Heavy Metal Content .....	5
	3.3.8 Halogen Content .....	5

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
4.	CORE CONSTRUCTION .....	5
4.1	TWIST LENGTH AND COLOR CODING OF PAIRED CONDUCTORS .....	5
	4.1.1 Pairs .....	5
	4.1.2 Pair Identification .....	5
4.2	ASSEMBLY OF PAIRED CONDUCTORS.....	6
	4.2.1 Core Layup .....	6
	4.2.2 Mirror Image .....	7
4.3	SPARE PAIRS.....	8
	4.3.1 Use .....	8
	4.3.2 Quantity .....	8
	4.3.3 Placement.....	8
4.4	BINDERS.....	9
4.5	CORE WRAP.....	9
5.	SHIELDS .....	9
5.1	MATERIAL.....	9
5.2	SHIELD APPLICATION .....	9
5.3	SHIELD SPLICES.....	9
6.	JACKET .....	9
6.1	JACKET MATERIAL .....	9
	6.1.1 Heavy Metal Free Jacket Material .....	9
6.2	JACKET THICKNESS.....	10
6.3	COMPLETED CABLE JACKET REQUIREMENTS .....	10
	6.3.1 Tensile Strength .....	10
	6.3.2 Elongation.....	10
	6.3.3 Heat Exposure (Aging) .....	10
6.4	JACKET COLOR .....	10
7.	ELECTRICAL REQUIREMENTS.....	10
7.1	ELECTRICAL CLASSIFICATIONS .....	10
7.2	MEASUREMENT PRECAUTION.....	10
7.3	DC RESISTANCE .....	10
7.4	DC RESISTANCE UNBALANCE .....	11
7.5	MUTUAL CAPACITANCE.....	11
7.6	PAIR-TO-PAIR CAPACITANCE UNBALANCE.....	11
7.7	PAIR-TO-GROUND CAPACITANCE UNBALANCE .....	11



TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	7.8 ATTENUATION .....	11
	7.9 NEAR END CROSSTALK.....	12
	7.9.1 Power Sum NEXT.....	12
	7.9.2 Subgroups .....	13
	7.10 FAR END CROSSTALK .....	13
	7.10.1 Power Sum EL FEXT.....	13
	7.10.2 Subgroups .....	14
	7.11 CHARACTERISTIC IMPEDANCE.....	14
	7.12 STRUCTURAL RETURN LOSS (SRL) .....	14
	7.13 PHASE DELAY .....	14
	7.14 PHASE DELAY SKEW .....	15
	7.15 INSULATION RESISTANCE .....	15
	7.16 CONDUCTOR-TO-CONDUCTOR DC PROOF TEST .....	15
	7.17 CORE-TO-SHIELD DC PROOF TEST .....	15
	7.18 AC LEAKAGE TEST .....	15
	7.19 CONTINUITY OF METALLIC CABLE ELEMENTS.....	15
8.	MECHANICAL REQUIREMENTS .....	15
	8.1 WIRE AND CABLE BEND TEST .....	15
	8.2 JACKET BONDING TEST .....	15
	8.3 CABLE PULLING TENSION.....	15
	8.4 FLAMMABILITY .....	15
	8.5 LIMITED SMOKE.....	16
	8.6 NATIONAL ELECTRICAL CODE.....	16
9.	GENERAL REQUIREMENTS.....	16
	9.1 IDENTIFICATION AND MARKING .....	16
	9.1.1 Method of Identification.....	16
	9.1.2 Length Marking.....	16
	9.2 JACKET INK MARKING DURABILITY .....	17

TABLES AND FIGURE

Table 2-1:	Conductor Diameters.....	3
Table 3-1:	Heavy Metal Free Insulation.....	4
Table 3-2:	Insulation Color.....	4
Table 4-1:	Pair Color Code.....	6
Table 4-2:	Unit Binder Color Code.....	7
Table 4-3:	Full Count Color Coding of Superunit Binders.....	7
Table 4-4:	Mirror Image Layer Color Code.....	8
Table 4-5:	Spare Pair Color Code.....	8
Table 6-1:	Heavy Metal Free Jacket Material.....	9
Table 7-1:	Maximum DC Resistance.....	11
Table 7-2:	Mutual Capacitance.....	11
Table 7-3:	Pair-To-Ground Capacitance Unbalance.....	11
Table 7-4:	Attenuation Constants.....	12
Table 7-5:	Maximum Attenuation.....	12
Table 7-6:	Power Sum Near End Crosstalk.....	13
Table 7-7:	Power Sum Equal Level Far End Crosstalk.....	14
Table 7-8:	Structural Return Loss.....	14
Table 1:	Specifications Referenced in This Standard.....	18
Figure A-1:	Wicking Test Configuration.....	21

APPENDICES

Appendix A:	Test Procedure for Wicking and Hygroscopicity.....	20
Appendix B:	Metallic Tape Splice Breaking Strength, Percent Retention.....	22
Appendix C:	Durability Test of Ink Markings.....	23

INFORMATIVE ANNEXES

Annex A:	Product Guide.....	A-1
Annex B:	ICEA Telecommunication Cable Standards.....	B-1

**ACRONYMS, ABBREVIATIONS AND SYMBOLS**

ANSI	American National Standards Association
ASTM	American Society for Testing and Materials
AWG	American Wire Gauge
$\alpha$	Attenuation
$^{\circ}\text{C}$	Degrees of Temperature, Celsius scale
CMG	UL Listing designation for General Purpose Communication Cable
CMR	UL Listing designation for Riser Communication Cable
$^{\circ}$	degrees symbol, temperature or angle
dc	Direct current
db	decibel
DOD	Diameter over dielectric
EIA	Electronics Industry Association
EL FEXT	Equal Level Far End Crosstalk
EPA	Environmental Protection Agency
$^{\circ}\text{F}$	Degrees of Temperature, Fahrenheit scale
FCC	Federal Communications Commission
f	frequency
FEXT	Far End Crosstalk
ft	foot or feet
FR	Federal Register
g	gram
ICEA	Insulated Cable Engineers Association
IEC	International Electro Commission
in	inch
$\text{in}^2$	Inches squared
IO FEXT	Input/Output Far End Crosstalk
ISO	International Standards Organization
kHz	kilohertz
%	percent
lbf	pound of force
LS	limited smoke
MHz	Megahertz
m	meter
$\text{m}^3$	cubic meter
mA	milliampere
ml	milliliter
mm	millimeter
MPa	megapascal
N	Newton
nf	nanofarad
NFPA	National Fire Protection Association
NEC	National Electrical Code
NEXT	Near End Crosstalk

**ACRONYMS, ABBREVIATIONS AND SYMBOLS -continued**

ns	nanosecond
oz	ounce
PS EL FEXT	Power Sum Equal Level Far End Crosstalk
PS NEXT	Power Sum Near End Crosstalk
pf	picofarad
ph	potential of hydrogen
ppm	part per million
psi	pounds per square inch
QuEST	Quality Excellence for Suppliers of Telecommunications
rms	root mean squared
SRL	Structural Return Loss
TCLP	Toxicity Characteristics Leaching Procedure
$\mu$ S	microsiemen
UL	Underwriters Laboratories

## **ICEA STANDARD FOR RISER CABLES TECHNICAL REQUIREMENTS**

### **SECTION 1 GENERAL**

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications cable specifications covering products intended for normal indoor premises use in the wiring systems of communications users. The parameters covered provide material, construction, and performance requirements.

Because this Standard does not cover all details of individual cable design, it cannot be used as a single document for procurement of product. This Standard is intended for use in conjunction with an individual product specification that provides complete design details for the specific cable type and designates the applicable performance requirements. Such individual cable specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical, electrical and flammability requirements for riser cables. Depending upon the application and system requirements, this Standard provides choices for materials and transmission characteristics.

For those characteristics where no differentiation is made, the performance requirements are applicable to all cables. Selection of the applicable type shall be at the discretion of the user and shall be designated in the product specification.

- 1.3 **OPTIONS AND INFORMATION:** This Standard is arranged in Sections covering specific areas of cable requirements and may be referenced as complete Sections or as individual paragraphs.

Riser cables are suitable for runs in vertical shafts of multi-story buildings. The typical cable construction is individually unshielded twisted pair of thermoplastic insulated copper conductors, with an overall 8-mil bonded aluminum shield and thermoplastic jacket. Such cables are typically available in pair counts from 25-3600.

These cables are intended for voice, text, data, video, and image transmission and are categorized by electrical transmission characteristics based on existing system requirements and projected application needs.

Historically, Riser cable transmission performance has been similar to Outside Plant requirements. Optionally, Category 3 performance may be chosen, and must be clearly marked. This Standard covers the minimum transmission performance requirements for the following classes of cable:

Class A: Intended for basic voice, text and data transmission with transmission characteristics specified to support T1 carrier transmission. These cables are referred to as ARxM, where "x" designates the conductor size; T for 26 AWG, M for 24 AWG and A for 22 AWG.

Class B: Intended for voice, text, data, video and image transmission with transmission characteristics specified for frequencies up to 16 MHz. These cables meet all requirements of a Category 3 cable.