

**ICEA STANDARD FOR
COAXIAL AND COAXIAL/TWISTED PAIR
COMPOSITE AERIAL SERVICE WIRES
TECHNICAL REQUIREMENTS**

Published By

INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Post Office Box 1568

Carrollton, Georgia 30112, U.S.A.

ICEA S-92-675-2005

© 2005 by ICEA

Approved June 8, 2005 by
Insulated Cable Engineers Association, Inc.

Approved November 29, 2005 by
American National Standard Institute, Inc.

Copyrighted by the ICEA
Contents may not be reproduced
in any form without permission of the
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

GLOBAL ENGINEERING DOCUMENTS
15 Inverness Way East
Englewood, CO 80113-5776, U.S.A.
Telephone: (800) 854-7179
www.global.ihs.com

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgements contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations, for safety or health purposes. Any certifications or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

(page intentionally left blank)

FOREWORD

ICEA Standards are published in the public interest and are intended to promote uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to this Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions for interpretation of ICEA Standards can only be accepted in writing and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary
Insulated Cable Engineers Association, Inc.
Post Office Box 1568
Carrollton, GA 30112, U.S.A.
United States of America

This Standard was approved by ICEA on June 8, 2005. The members of the ICEA Communications Cable Division, Working Group 675, who participated in this project were:

D. K. Baker
J. Kincaid

L. Hazy
B. Pope

T. Zou
K. Chauvin

The following participated in an advisory capacity to Working Group 675:

G. Hessler RUS

TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
1	<u>GENERAL</u>	
	1.1 Purpose	1
	1.2 Scope.....	1
	1.3 Options and Information	2
	1.4 Units and Tolerances	2
	1.5 References	2
	1.6 Quality Assurance.....	2
	1.7 Safety Considerations.....	3
2	<u>CONDUCTORS</u>	
	2.1 Twisted Pair Conductors.....	3
	2.1.1 Requirements.....	3
	2.1.2 Factory Joints.....	3
	2.2 Conductors of Coaxial Unit.....	3
	2.2.1 Center Conductor of Coaxial Unit	3
	2.2.1.1 Resistance Requirements.....	3
	2.2.1.2 Tensile and Elongation Requirements	4
	2.2.1.3 Factory Joints	4
	2.2.2 Outer Conductor (Shield) of Coaxial Unit.....	4
	2.2.2.1 Shielding Tape.....	5
	2.2.2.2 Braid	5
	2.2.2.3 Outer Shield.....	6
	2.2.2.4 Outer Braid	6
3	<u>CONDUCTOR INSULATION</u>	
	3.1 Conductor Insulation for Twisted Pairs	6
	3.1.1 Insulation Material.....	6
	3.1.2 Insulation Type.....	6
	3.1.3 Insulation Dimensions and Colors	6
	3.1.4 Splices	7
	3.1.5 Insulation Physical Requirements.....	7
	3.1.5.1 Adhesion.....	7
	3.1.5.2 Elongation.....	7
	3.1.5.3 Cold Bend	7
	3.1.5.4 Shrinkback.....	7
	3.1.5.5 Thermal Oxidative Stability.....	8
	3.1.5.6 Heat exposure (aging)	8
	3.1.6 Spark Test.....	8
	3.1.7 Twist Length and Color Coding.....	8

TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
	3.2 Conductor Insulation for Center Conductor of Coaxial Unit.....	9
	3.2.1 Insulation Material.....	9
	3.2.2 Insulation Type.....	9
	3.2.3 Insulation Dimension.....	9
	3.2.4 Insulation Physical Requirements.....	9
	3.2.4.1 Adhesion.....	9
	3.2.4.2 Thermal Oxidative Stability – OIT Test of Foam Dielectric.....	10
	3.2.4.3 Shrinkback.....	10
4	<u>STRENGTH MEMBER / MESSENGER</u>	
	4.1 Strength Member / Messenger Options.....	10
	4.2 Steel Reinforcement.....	10
	4.2.1 Galvanized Steel Messenger.....	10
	4.2.2 Tensile Strength.....	10
	4.2.3 Splicing.....	11
	4.3 Synthetic Reinforcement.....	11
	4.3.1 Non Metallic Strength Member.....	11
	4.3.2 Splicing.....	11
5	<u>JACKET CONFIGURATION</u>	
	5.1 Design Options.....	11
	5.1.1 Single Coaxial Unit.....	11
	5.1.2 Joint Core.....	11
	5.1.3 Composite/Hybrid or Butterfly Design.....	11
	5.2 Core Wrap.....	11
	5.3 Rip Cord.....	11
6	<u>JACKET</u>	
	6.1 Jacket Material.....	13
	6.2 Jacket Thickness.....	13
	6.3 Jacket Eccentricity.....	13
	6.4 Diameter over Coax-Jacket.....	14
	6.5 Completed Wire Jacket Requirements.....	14
	6.5.1 Tensile Strength.....	15
	6.5.2 Elongation.....	15
	6.5.3 Heat Exposure (Aging).....	15
	6.5.4 Light Absorption.....	15

TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
7	<u>ELECTRICAL REQUIREMENTS</u>	
	7.1 Electrical Requirements of Twisted Pairs	15
	7.1.1 Continuity	15
	7.1.2 Conductor Resistance.....	15
	7.1.3 Resistance Unbalance	15
	7.1.4 Mutual Capacitance	15
	7.1.5 Pair-to-Pair Capacitance Unbalance.....	16
	7.1.6 Pair-to-Ground Capacitance Unbalance	16
	7.1.7 Attenuation-Dry	16
	7.1.8 Attenuation-Wet	16
	7.1.9 Crosstalk	16
	7.1.10 Insulation Resistance-Wet	16
	7.1.11 Dielectric Strength-Dry	17
	7.1.12 Fusing Coordination.....	17
	7.2 Electrical Requirements of Coaxial Unit	17
	7.2.1 Continuity	17
	7.2.2 Conductor Resistance.....	17
	7.2.3 Insulation Resistance.....	17
	7.2.4 Dielectric Strength.....	17
	7.2.5 Characteristic Impedance	17
	7.2.6 Structural Return Loss	18
	7.2.7 Shielding Effectiveness.....	18
	7.2.8 Attenuation.....	18
	7.2.9 Velocity of Propagation	18
	7.2.10 Heat Aging Test	18
8	<u>MECHANICAL REQUIREMENTS</u>	
	8.1 Impact Test-Unaged	19
	8.2 Impact Test-Aged	20
	8.3 Static Load Test.....	20
	8.4 Plasticizer Compatibility.....	20
	8.5 Compatibility of Jacket and Fiber Adhesive (NMR)	20
	8.6 Abrasion Resistance.....	20
	8.7 Cold Temperature Handling-Unaged.....	21
	8.8 Cold Temperature Handling-Aged.....	21
	8.9 Web Separation	22
	8.9.1 Room Temperature Separation	22
	8.9.2 Low Temperature Separation	22
	8.10 National Electrical Code	22

TABLE OF CONTENTS

CONTENTS	SECTION	PAGE
9	<u>MARKING AND PACKAGING</u>	
	9.1 Jacket Marking.....	22
	9.2 Length Marking.....	23
	9.3 Jacket Ink Marking Durability.....	23
	9.4 End-Sealing.....	23
	9.5 Packaging.....	23

TABLES

Table 2-1	Conductivity and DC Resistance of Center Conductor – Coaxial Unit.....	4
Table 2-2	Elongation and Tensile Strength of Center Conductor – Coaxial Unit.....	4
Table 2-3	Diameter of Outer Conductor – Coaxial Unit.....	5
Table 3-1	Conductor Insulation Color – Twisted Pairs.....	7
Table 3-2	Twisted Pair Color Code.....	8
Table 3-3	Diameter and Eccentricity of Center Conductor Insulation – Coaxial Unit.....	9
Table 3-4	Center Conductor Insulation Adhesion – Coaxial Unit.....	9
Table 4-1	Diameter – Galvanized Steel Messengers.....	10
Table 6-1	Diameter Over Jacket – Coaxial Unit.....	14
Table 7-1	Loop Resistance – Coaxial Unit.....	17
Table 7-2	Attenuation Requirements – Coaxial Unit.....	19
Table I	Specifications Referenced in this Standard.....	24
Table D-1	Test Current and Current Duration – Fusing Coordination Test.....	33

FIGURES

Figure 5-1:	- Hybrid Composite and Butterfly Designs.....	12
Figure 5-2:	- Figure 8 Design.....	12
Figure 6-1	– Jacket Thickness Measurement Method Standard and Quad Shielded Coaxial Wires.....	14
Figure A-1	– Wicking Test Configuration.....	28
Figure D-1	– Fusing Coordination Test Configuration.....	33

APPENDICES

Appendix A	Test Procedure For Wicking and Hygroscopicity.....	27
Appendix B	Jacket Rip Cord Test.....	29
Appendix C	Solution Method to Determine “Apparent” Absorption Coefficient for PVC Materials.....	30
Appendix D	Fusing Coordination Test.....	32

ACRONYMS, ABBREVIATIONS AND SYMBOLS

A	apparent absorption coefficient
ac	alternating current
ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
AWG	American Wire Gauge
°C	degrees of temperature, Celsius scale
CAS	Chemical Abstract Services
dB	decibels
dc	direct current
EIA	Electronics Industry Alliance
°F	degrees of temperature, Fahrenheit scale
ft	foot or feet
g	gram(s)
Hz	Hertz
ICEA	Insulated Cable Engineers Association
ISDN	Integrated Services Digital Network
ISO	International Organization for Standardization
kft	kilofeet or kilofeet
kg	kilogram
kHz	kilohertz
km	kilometer
kPa	kilopascal
LAN	Local Area Network
lbf	pound of force
m	meter
Mb	megabits
mg	milligram
MHz	megahertz
min.	minimum
ml	milliliter
mm	millimeter
mm ²	square millimeter
MPa	megapascal
N	Newton
NESC	National Electrical Safety Code
NFPA	National Fire Protection Association
nF	nanofarad
NID	Network Interface Device
NIU	Network Interface Unit
%	percent
pF	picofarad
POTS	Plain Old Telephone Service
psi	pounds per square inch
PVC	polyvinyl chloride
RF	radio frequency
rms	root-mean-square

ACRONYMS, ABBREVIATIONS AND SYMBOLS - continued

SCTE	Society of Cable Telecommunication Engineers
sec	second
T1	North American Digital Hierarchy Line Code – Equivalent to 1.544 Mb/sec
UL	Underwriters Laboratories
V	volt
WAN	Wide Area Network
~	approximation symbol
°	degrees symbol, temperature or angle
"	inches or inch symbol

COAXIAL AND COAXIAL/TWISTED PAIR COMPOSITE AERIAL SERVICE WIRES TECHNICAL REQUIREMENTS

SECTION 1 GENERAL

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications wire specifications covering products intended for the aerial outside plant use. The parameters covered provide material, construction, and performance requirements.

Because this Standard does not cover all details of individual wire designs, it cannot be used as a single document for procurement of product. This Standard is intended to be used in conjunction with an individual product specification that provides complete design details for the specific wire type and designates the applicable performance requirements. Such individual wire specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical and electrical requirements of service wires containing at least one coaxial core and optionally up to six twisted pairs, used for service applications to extend the telephone/multimedia circuit from the distribution terminal to the subscriber's station protector NID (Network Interface Device) or protected NIU (Network Interface Unit).

Furthermore, a distinction between **Type I** and **Type II** is made with regard to transmission characteristics and shielding materials of the coaxial unit.

Aerial Service Wire is intended to be self supporting and shall contain strength members to accommodate the appropriate requirements of this Standard. The self supporting properties may be accomplished by utilizing a zinc coated steel strength member or synthetic fibers as strength members embedded in a suitably shaped jacket.

The coaxial unit is intended to be used for either RF or compressed digital video and radio transmissions. This unit shall also allow bi-directional traffic. The coaxial unit should also be capable of carrying high speed digital signals for LAN/WAN applications (such as T1, ISDN, etc.) as well as POTS (Plain Old Telephone Services). The network supporting these protocols will be based upon physical lines having a characteristic impedance of 75 Ohms. The coaxial units are specified in three and four common sizes for **Type I** and **Type II** respectively, to accommodate different drop lengths.

The twisted pair wires are intended for voice and data transmission and their characteristics are based upon existing system requirements and projected application needs.