

**STANDARD FOR**  
**BROADBAND TWISTED PAIR CABLE**  
**AIRCORE, POLYOLEFIN INSULATED, COPPER CONDUCTOR**  
**TECHNICAL REQUIREMENTS**

Published By  
**INSULATED CABLE ENGINEERS ASSOCIATION, INC.**  
Post Office Box 1568  
Carrollton, GA 30112, U.S.A.

© 2006 by ICEA

Approved September 14, 2006 by  
Insulated Cable Engineers Association

Approved January 4, 2007 by  
American National Standards Institute

Copyrighted by the ICEA  
Contents may not be reproduced  
in any form without permission of the  
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

GLOBAL ENGINEERING DOCUMENTS  
15 Inverness Way East  
Englewood, CO 80113-5776 USA  
Telephone: (800) 854-7179  
[www.global.ihs.com](http://www.global.ihs.com)

## NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgements contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certifications or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

## FOREWORD

ICEA Standards are published in the public interest and are intended to promote product uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions of interpretation of ICEA Standards can only be accepted in writing- and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to

Secretary  
Insulated Cable engineers Association  
P.O. Box 1568  
Carrollton, GA 30112  
United States of America

This Standard was developed by the ICEA Communications Cable Division, Working Group 688. It was approved by ICEA on September 14, 2006. It and its companion standard S-99-689, were patterned after existing ICEA Standards, i.e. S-85-625 and S-84-608, respectively.

The members of the ICEA Communications Cable Section, Working Group 688, who participated in this project, were:

D. K. Baker  
J. Kincaid

G. L. Dorna  
R. Lovie  
T. Zou

L. Hazy  
T. McLaughlin

**TABLE OF CONTENTS**

<b>CONTENTS:</b>	<b>SECTION</b>	<b>PAGE</b>
	1. GENERAL	
	1.1 Purpose .....	1
	1.2 Scope .....	1
	1.3 Options and Information .....	1
	1.4 Units and Tolerances.....	2
	1.5 References .....	2
	1.6 Quality Assurance .....	2
	1.7 Safety Considerations .....	3
	2. CONDUCTORS	
	2.1 Requirements .....	3
	2.2 Factory Joints .....	4
	3. CONDUCTOR INSULATION	
	3.1 Insulation Material .....	4
	3.1.1 High-Density Polyethylene.....	4
	3.1.2 Medium-Density Polyethylene .....	4
	3.1.3 Polypropylene .....	4
	3.2 Insulation Type .....	4
	3.2.1 Solid.....	4
	3.2.2 Foam.....	4
	3.2.3 Foam-Skin .....	4
	3.3 Insulation Dimensions, Colors, and Splices .....	4
	3.4 Insulation Physical Requirements.....	5
	3.4.1 Insulation Adhesion.....	5
	3.4.2 Elongation.....	5
	3.4.3 Compression.....	5
	3.4.4 Cold Bend .....	6
	3.4.5 Shrinkback .....	6
	3.4.6 Thermal Oxidative Stability .....	6
	3.5 Twist Length and Color Coding .....	6

**TABLE OF CONTENTS**

<b>CONTENTS:</b>	<b>SECTION</b>	<b>PAGE</b>
4.	CORE CONSTRUCTION	
4.1	Core Assembly .....	7
4.1.1	Cables with 25 Pairs or Less .....	7
4.1.2	Cables with more than 25 Pairs .....	7
4.1.3	Super-Units.....	8
4.2	Binders .....	8
4.2.1	Binder Lay.....	8
4.2.2	Missing Binder .....	8
4.2.3	Binder Shrinkback.....	9
4.3	Spare Pairs.....	9
4.4	Fillers.....	9
4.5	Core Wrap .....	9
4.6	Self-Support (Figure 8) Cable.....	10
4.6.1	Support Messenger .....	10
4.6.2	Dimensions .....	10
4.6.3	Reinforced Self-Support.....	10
4.7	Flooding Compound .....	10
5.	INTERNAL SCREENS	
6.	SHIELDS	
6.1	Shielding Systems .....	10
6.2	Shield Materials .....	11
6.2.1	8-mil Bare Aluminum Tape .....	11
6.2.2	8-mil Coated Aluminum Tape .....	11
6.2.3	5-mil Copper Tape .....	11
6.2.4	5-mil Copper Clad Alloy Steel Tape .....	11
6.2.5	5-mil Copper Clad Stainless Steel Tape .....	11
6.2.6	6- and 7-mil 194 Copper Alloy Tape.....	12
6.2.7	5-mil C230 Copper alloy.....	12
6.2.8	6-mil Bare Steel Tape .....	12
6.2.9	6-mil Coated Steel Tape .....	12
6.3	Shield Application .....	13
6.3.1	Shield Corrugation .....	13
6.3.2	Residue Forming/Corrugating Oil .....	13
6.3.3	Shield Overlap .....	13
6.3.4	Shield Splices .....	13

**TABLE OF CONTENTS**

<b>CONTENTS:</b>	<b>SECTION</b>	<b>PAGE</b>
	6.4 Corrugation Extensibility .....	14
	<b>7. POLYETHYLENE INNER AND OUTER JACKET</b>	
	7.1 Inner Jacket .....	15
	7.1.1 Material and Test Requirements .....	15
	7.1.2 Inner Jacket Thickness Requirement .....	15
	7.2 Outer Jacket .....	15
	7.2.1 Raw Material .....	15
	7.2.2 Completed Cable Jacket Material Requirement .....	16
	7.2.3 Completed Cable Material Requirements .....	16
	7.2.4 Shrinkback .....	17
	7.2.5 Sheath Adherence - Bonded .....	17
	<b>8. ELECTRICAL REQUIREMENTS</b>	
	8.1 Measurement Precaution .....	18
	8.2 DC Resistance .....	18
	8.3 DC Resistance Unbalance .....	18
	8.4 Mutual Capacitance .....	18
	8.5 Pair-to-Ground Capacitance Unbalance .....	19
	8.6 Characteristic Impedance .....	19
	8.7 Return Loss .....	19
	8.8 Attenuation .....	19
	8.8.1 Attenuation at Elevated Temperatures .....	20
	8.9 Delay and Differential Delay (Skew) .....	20
	8.9.1 Delay .....	20
	8.9.2 Differential Delay (Skew) .....	20
	8.10 Crosstalk .....	20
	8.10.1 Unit Crosstalk (NEXT) .....	21
	8.10.2 Unit Crosstalk (ELFEXT) .....	21
	8.10.3 Inter Unit Crosstalk .....	22
	8.10.4 Spare Pairs .....	22
	8.11 Insulation Resistance .....	22
	8.12 Conductor-To-Conductor DC Proof Test .....	22
	8.13 Core-To-Shield DC Proof Test .....	22
	8.14 Core-To-Screen DC Proof Test .....	23
	8.15 Shield Resistance .....	23
	8.16 Continuity of Metallic Cable Elements .....	23

**TABLE OF CONTENTS**

<b>CONTENTS:</b>	<b>SECTION</b>	<b>PAGE</b>
	9. MECHANICAL REQUIREMENTS	
	9.1 Cable Bend Test.....	23
	9.1.1 Cold Bend Test.....	23
	9.1.2 Hot Bend Test.....	23
	9.2 Cable Impact.....	23
	9.3 Jacket Notch Test for Steel Shielded Cable.....	23
	9.4 Cable Torsion.....	24
	10. GENERAL REQUIREMENTS	
	10.1 Identification and Marking.....	25
	10.1.1 Manufacturer Identification.....	25
	10.1.2 Year of Manufacture.....	25
	10.1.3 Alternate Identification.....	26
	10.1.4 Jacket Marking.....	26
	10.1.5 Length Marking.....	26
	10.1.6 Defective or Nonconforming Pair Marking.....	27
	10.1.7 Communication Cable Identifier.....	27
	10.2 End Sealing.....	27
	10.3 Information Accompanying the Reel.....	27
	10.4 Pressurization.....	27
	10.5 Optional Requirements.....	28
	10.5.1 Physical Reel Protection.....	28
	10.5.2 Pulling Eyes.....	28

**TABLE OF CONTENTS****CONTENTS: PAGE****TABLES**

Table 2-1:	Nominal Conductor Diameter .....	3
Table 2-2:	Minimum Conductor Elongation .....	4
Table 3-1:	Insulation Colors.....	5
Table 3-2:	Minimum Compressive Strength .....	5
Table 3-3:	Color Code .....	7
Table 4-1:	Unit Binder Color Code.....	8
Table 4-2:	Spare Pair Colors .....	9
Table 6-1:	Tape Thickness .....	12
Table 6-2:	Steel Composition .....	12
Table 6-3:	Shield Tape Tensile Load.....	14
Table 7-1:	Inner Jacket Thickness.....	15
Table 7-2:	Outer Jacket Thickness .....	16
Table 7-3:	Completed Cable Jacket Material Requirements .....	17
Table 8-1:	DC Resistance.....	18
Table 8-2:	Return Loss Values .....	19
Table 8-3:	Attenuation Constants .....	19
Table 8-4:	Attenuation .....	20
Table 8-5:	PS NEXT and PS ELFEXT .....	22
Table 8-6:	DC-Proof Test.....	22
Table 10-1:	Year Marker Color Code.....	25
Table 10-2:	Pulling Eye Load Factors.....	28
Table I:	Specifications Referenced in This Standard.....	29

**FIGURES**

Figure 1-A:	Polyethylene Jacket Thickness Requirements for Self-Support (Figure 8) Cable - Option A .....	31
Figure 1-B:	Polyethylene Jacket Thickness Requirements for Self-Support (Figure 8) Cable - Option B .....	32
Figure 1-C	Polyethylene Jacket Thickness Requirements for Reinforced Self-Support (Figure 8) Cable .....	33
Figure 2:	Forming of Steel Tape Overlap .....	34
Figure 3:	Minimum Extensibility (EXT) for Aluminum .....	35
Figure 4:	Minimum Extensibility (EXT) for Steel .....	36
Figure 5:	Sample Preparation for Notch Test.....	37
Figure A-1	Wicking Test Configuration.....	39

**APPENDICES**

Appendix A:	Wicking and Hygroscopicity Test Procedures .....	38
Appendix B:	Metallic Tape Splice Breaking Strength, Percent Retention .....	40

**TABLE OF CONTENTS**

**CONTENTS:** **PAGE**

ANNEX

Informative Annex A: Product Guide.....	A-1
Informative Annex B: ICEA Telecommunication Cable Standards.....	B-1

## ACRONYMS, ABBREVIATIONS AND SYMBOLS (Used in this Standard)

ac	-	alternating current
ANSI	-	American National Standards Institute
ASTM	-	American Society for Testing and Materials
AWG	-	American Wire Gauge
BB-ASW	-	broadband aerial service wire
CAS	-	Chemical Abstract Service
CUPP	-	capacitance unbalance pair to pair
dc	-	direct current
EIA	-	Electronics Industries Alliance
ELFEXT	-	equal level far end crosstalk
FEXT	-	far end crosstalk
ft	-	foot, feet
hrs	-	hours
ICEA	-	Insulated Cable Engineers Association
In	-	inch
IO FEXT	-	input to output far end crosstalk
k1, k2, k3	-	coefficients to calculate the attenuation
kHz	-	kilo- Hertz
kV	-	kilovolt
L	-	length of wire for which electrical results are reported
lbf	-	pound-force
NEXT	-	near end crosstalk
NIST	-	National Institute of Standards and Technology
OIT	-	oxidative induction time
PS ELFEXT	-	power sum equal level far-end crosstalk
PS NEXT	-	power sum near-end crosstalk
psi	-	pounds per square inch
PVC	-	polyvinyl chloride
s	-	second
SI	-	International System of Units
TIA	-	Telecommunication Industry Association
TV	-	television
$\alpha$	-	attenuation per unit length
$\rho$	-	density
$\Omega$	-	Ohm
$^{\circ}$	-	degree
%	-	percent

(page intentionally left blank)

**ICEA STANDARD FOR  
BROADBAND TWISTED PAIR CABLE  
AIRCORE, POLYOLEFIN INSULATED, COPPER CONDUCTOR  
TECHNICAL REQUIREMENTS**

**SECTION 1 GENERAL**

- 1.1 **PURPOSE:** The purpose of this Standard is to establish generic technical requirements that may be referenced by individual telecommunications cable specifications covering products intended for broadband outside plant use. The parameters covered provide material, construction, and performance requirements that are applicable to aircore, polyolefin insulated and jacketed cables of limited pair counts, including a variety of shield and jacket combinations.

Because this Standard does not cover all details of individual cable design, it cannot be used as a single document for procurement of product. It is intended to be used in conjunction with an individual product specification that provides complete design details for the specific cable type and designates the applicable performance requirements. Such individual cable specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical and electrical requirements for aircore broadband twisted pair telecommunications cable with polyolefin insulated copper conductors.

Broadband cables as described in this Standard are primarily intended to supply broadband services from the remote switch to the customer premises. The remote switch in turn is normally supplied by fiber link from the central office. The reach of these systems is a function of the signal to noise ratio, deployed protocol and bit-rate, and may exceed 1000 m (3280 ft). These systems will allow the simultaneous transmission of regular telephone services, computer, fax and several TV channels. The TV services may be interactive or may be High Definition TV.

- 1.3 **OPTIONS AND INFORMATION:** This Standard provides alternative choices for type of insulation, core assembly, color code, sheath design (shielding materials, single or double jackets, and jacket thicknesses and materials).

One of the objectives of this Standard is to ensure compatibility with the Category 5e system requirements as specified in the TIA/EIA Standard 568-B.2 for commercial building telecommunications cabling, so that the standardized cables can be used as "Customer Owned Outside Plant Cables" or "Campus Cables".

These cables are intended to be installed aerially. When properly pressurized, they may also be installed in ducts or directly buried.

This Standard is arranged in Sections. Each Section covers one specific area of cable requirement and may be referenced as complete Sections or as individual paragraphs.

Paragraphs in this Standard where the user may specify a particular option are listed below:

- 2.1 Conductor Size
- 3.2 Insulation Type
- 4.6 Self-Support (Figure 8) Cable
- 6.1 Shielding Systems
- 6.3 Shield Application
- 7.1 Inner Jacket
- 7.2.1 Outer Jacket (Material Type)
- 10.1.5 Length Marking
- 10.4 Pressurization
- 10.5.1 Physical Reel Protection
- 10.5.2 Pulling Eyes

**To assist the user in selection of options and to avoid possible misunderstandings between the manufacturer and user, it is suggested that a check-off sheet similar to that shown in Informative Annex A be utilized.**

- 1.4 **UNITS AND TOLERANCES:** SI units (see NIST-SP 811) are specified throughout this Standard except for conductor size. Approximate US equivalents and Fahrenheit temperatures are included for information only. The rounding-off method of ASTM E 29 shall be used for determining measurement tolerances.
- 1.5 **REFERENCES:** All documents referenced herein shall be as listed in Table I with issues or dates as indicated.
- 1.6 **QUALITY ASSURANCE:** It is the responsibility of the manufacturer to establish a quality assurance system consistent with ISO Q9001, or an alternate system acceptable to the user. When the user wishes to require a specific quality assurance program or special testing procedures, agreement between the user and the manufacturer should be reached before the order is placed.

Requirements provided in this Standard are of two types, qualification and product performance. Qualification requirements are intended to be proof of adequate design and processing and shall be repeated as needed for verification. Product performance requirements are those which shall be met by every length of delivered cable as assured by quality control methods. The following tests shall be performed on all completed cables. The term "completed cable" refers to a continuous length of finished cable resulting from the last jacketing operation.

Properties that shall be tested on 100 percent of the cable lengths produced are listed below by paragraph number:

1. Jacket Thickness per Paragraph 4.6.2, 4.6.3, 7.1.2 and 7.2.2
2. Conductor-to-Conductor DC Proof Test per Paragraph 8.12
3. Core-to-Shield DC Proof Test per Paragraph 8.13
4. Core-to-Screen DC Proof Test per Paragraph 8.14
5. Continuity of Metallic Cable Elements per Paragraph 8.16

- 1.7 SAFETY CONSIDERATIONS: Materials in the cable shall present no dermal or environmental hazards as defined by current industry standards or applicable federal or state laws and regulations.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.